

Product fiche

HEAT PUMP SPACE HEATER		Outdoor	AQS120X1o
		Indoor	AQS160X13i
Indoor unit sound power (*)		[dB(A)]	43.0
Outdoor unit sound power (*)	Average climate low temperature application	[dB(A)]	64.0
	Average climate medium temperature application	[dB(A)]	64.0
Capacity of the backup heater integrated in the unit	P _{sup} back-up heater (optional)	[kW]	0/3/9
Space heating	Energy efficiency class 35°C (Low temp. app.)	-	A+++
Space heating	Energy efficiency class 55°C (Medium temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Space heating 35°C	P _{rated} (declared heating capacity) @ -10°C	[kW]	12.0
	Seasonal space heating efficiency (η _s)	[%]	189.4
	Annual energy consumption	[kWh]	5,152
Space heating 55°C	P _{rated} (declared heating capacity) @ -10°C	[kW]	11.6
	Seasonal space heating efficiency (η _s)	[%]	135.1
	Annual energy consumption	[kWh]	6,927
Part load conditions space heating average climate low temperature application			
(A) condition (-7°C)	P _{th} (declared heating capacity)	[kW]	10.61
	COP _d (declared COP)	-	2.88
	C _{th} (degradation coefficient)	-	0.00
(B) condition (2°C)	P _{th} (declared heating capacity)	[kW]	6.69
	COP _d (declared COP)	-	4.65
	C _{th} (degradation coefficient)	-	0.00
(C) condition (7°C)	P _{th} (declared heating capacity)	[kW]	4.44
	COP _d (declared COP)	-	6.62
	C _{th} (degradation coefficient)	-	0.00
(D) condition (12°C)	P _{th} (declared heating capacity)	[kW]	3.74
	COP _d (declared COP)	-	8.47
	C _{th} (degradation coefficient)	-	0.90
(E) TOL (temperature operating limit)	TOL (temperature operating limit)	[°C]	-10.00
	P _{th} (declared heating capacity)	[kW]	10.74
	COP _d (declared COP)	-	2.77
	W _{TOL} (Heating w ater Operation Limit)	[°C]	60.00
(F) Tivalent temperature	Tblv	[°C]	-7.00
	P _{th} (declared heating capacity)	[kW]	10.61
	COP _d (declared COP)	-	2.88
Supplementary capacity at P _{design}	P _{sup} (@Tdesignh: -10°C)	[kW]	1.26
Part load conditions space heating average climate medium temperature application			
(A) condition (-7°C)	P _{th} (declared heating capacity)	[kW]	10.24
	COP _d (declared COP)	-	2.01
	C _{th} (degradation coefficient)	-	0.00
(B) condition (2°C)	P _{th} (declared heating capacity)	[kW]	6.52
	COP _d (declared COP)	-	3.44
	C _{th} (degradation coefficient)	-	0.00
(C) condition (7°C)	P _{th} (declared heating capacity)	[kW]	4.36
	COP _d (declared COP)	-	4.59
	C _{th} (degradation coefficient)	-	0.00
(D) condition (12°C)	P _{th} (declared heating capacity)	[kW]	3.29
	COP _d (declared COP)	-	6.05
	C _{th} (degradation coefficient)	-	0.90
(E) TOL (temperature operating limit)	TOL (temperature operating limit)	[°C]	-10.00
	P _{th} (declared heating capacity)	[kW]	9.10
	COP _d (declared COP)	-	1.79
	W _{TOL} (Heating w ater Operation Limit)	[°C]	60.00
(F) Tivalent temperature	Tblv	[°C]	-7.00
	P _{th} (declared heating capacity)	[kW]	10.27
	COP _d (declared COP)	-	2.01
Supplementary capacity at P _{design}	P _{sup} (@Tdesignh: -10°C)	[kW]	2.50